

LOAN DOCUMENT

DTIC ACCESSION NUMBER	<div style="border: 1px solid black; width: 100px; height: 80px; margin: 0 auto;"></div> <p>LEVEL</p>	<p>PHOTOGRAPH THIS SHEET</p>	<div style="border: 1px solid black; width: 100px; height: 80px; margin: 0 auto; display: flex; align-items: center; justify-content: center;"> </div> <p>INVENTORY</p>																												
	<div style="border: 1px solid black; padding: 10px; margin: 0 auto; width: 80%;"> <p style="font-size: 1.5em; font-family: cursive;">WL-TR-96-2087</p> <p>DOCUMENT IDENTIFICATION</p> </div>																														
	<div style="border: 1px solid black; padding: 10px; margin: 0 auto; width: 80%;"> <p style="border: 1px solid black; padding: 5px; display: inline-block;">DISTRIBUTION STATEMENT A</p> <p style="margin-top: 5px;">Approved for public release Distribution unlimited</p> </div> <p>DISTRIBUTION STATEMENT</p>																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 2px;">ACCESSION FOR</td> </tr> <tr> <td style="padding: 2px;">NTIS</td> <td style="padding: 2px;">GRAM <input checked="" type="checkbox"/></td> </tr> <tr> <td style="padding: 2px;">DTIC</td> <td style="padding: 2px;">TRAC <input type="checkbox"/></td> </tr> <tr> <td colspan="2" style="padding: 2px;">UNANNOUNCED <input type="checkbox"/></td> </tr> <tr> <td colspan="2" style="padding: 2px;">JUSTIFICATION</td> </tr> <tr><td colspan="2" style="height: 15px;"></td></tr> <tr><td colspan="2" style="height: 15px;"></td></tr> <tr><td colspan="2" style="height: 15px;"></td></tr> <tr><td colspan="2" style="height: 15px;"></td></tr> <tr> <td colspan="2" style="padding: 2px;">BY</td> </tr> <tr> <td colspan="2" style="padding: 2px;">DISTRIBUTION/</td> </tr> <tr> <td colspan="2" style="padding: 2px;">AVAILABILITY CODES</td> </tr> <tr> <td style="padding: 2px;">DISTRIBUTION</td> <td style="padding: 2px;">AVAILABILITY AND/OR SPECIAL</td> </tr> <tr> <td style="height: 80px; vertical-align: bottom; text-align: center; font-size: 2em;">A-1</td> <td></td> </tr> </table> <p style="text-align: center; margin-top: 5px;">DISTRIBUTION STAMP</p>				ACCESSION FOR		NTIS	GRAM <input checked="" type="checkbox"/>	DTIC	TRAC <input type="checkbox"/>	UNANNOUNCED <input type="checkbox"/>		JUSTIFICATION										BY		DISTRIBUTION/		AVAILABILITY CODES		DISTRIBUTION	AVAILABILITY AND/OR SPECIAL	A-1	
ACCESSION FOR																															
NTIS	GRAM <input checked="" type="checkbox"/>																														
DTIC	TRAC <input type="checkbox"/>																														
UNANNOUNCED <input type="checkbox"/>																															
JUSTIFICATION																															
BY																															
DISTRIBUTION/																															
AVAILABILITY CODES																															
DISTRIBUTION	AVAILABILITY AND/OR SPECIAL																														
A-1																															
		<p>DATE ACCESSIONED</p>																													
		<p>DATE RETURNED</p>																													
		<p>REGISTERED OR CERTIFIED NUMBER</p>																													

A-1

19960812 160

DATE RECEIVED IN DTIC

PHOTOGRAPH THIS SHEET AND RETURN TO DTIC-FDAC

HANDLE WITH CARE

WL-TR-96-2087



**LOW REYNOLDS NUMBER TURBINE
BLADE CASCADE CALCULATIONS**

**Richard Rivir
Rolf Sondergaard
Michael Dahlstrom
Elizabeth Ervin**

1996

FINAL REPORT 1 NOVEMBER 1995--9 JULY 1996

Approved for public release; distribution unlimited

**AERO PROPULSION & POWER DIRECTORATE
WRIGHT LABORATORY
AIR FORCE MATERIEL COMMAND
WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-7650**

This paper is declared a work of the U.S. Government and as such is not subject to copyright protection in the United States

NOTICE

WHEN GOVERNMENT DRAWINGS, SPECIFICATIONS, OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY GOVERNMENT-RELATED PROCUREMENT, THE UNITED STATES GOVERNMENT INCURS NO RESPONSIBILITY OR ANY OBLIGATION WHATSOEVER. THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA, IS NOT TO BE REGARDED BY IMPLICATION, OR OTHERWISE IN ANY MANNER CONSTRUED, AS LICENSING THE HOLDER, OR ANY OTHER PERSON OR CORPORATION; OR AS CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE, OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

THIS REPORT IS RELEASABLE TO THE NATIONAL TECHNICAL INFORMATION SERVICE (NTIS). AT NTIS, IT WILL BE AVAILABLE TO THE GENERAL PUBLIC, INCLUDING FOREIGN NATIONS.


THE TECHNICAL REPORT HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION.



RICHARD B. RIVIR
Manager, Aerothermal Research
Turbine Branch
Turbine Engine Division
Aero Propulsion & Power Directorate



CHARLES D. MACARTHUR
Chief
Turbine Branch
Turbine Engine Division
Aero Propulsion & Power Directorate



RICHARD J. HILL
Chief of Technology
Turbine Engine Division
Aero Propulsion & Power Directorate

IF YOUR ADDRESS HAS CHANGED, IF YOU WISH TO BE REMOVED FROM OUR MAILING LIST, OR IF THE ADDRESSEE IS NO LONGER EMPLOYED BY YOUR ORGANIZATION PLEASE NOTIFY WL/POTT, WPAFB OH 45433-7650 TO HELP MAINTAIN A CURRENT MAILING LIST.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 1996	3. REPORT TYPE AND DATES COVERED Final 1 Nov 95 - 9 Jul 96		
4. TITLE AND SUBTITLE Low Reynolds Number Turbine Blade Cascade Calculations		5. FUNDING NUMBERS PE 61102F JON 2307S315		
6. AUTHOR(S) Richard B. Rivir, Rolf Sondergaard, Michael Dahlstrom, Elizabeth Ervin				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Aero Propulsion & Power Directorate Wright Laboratory Air Force Materiel Command Wright-Patterson Air Force Base, OH 45433-7650		8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Aero Propulsion & Power Directorate Wright Laboratory Air Force Materiel Command Wright-Patterson Air Force Base, OH 45433-7650 POC: Richard B Rivir, WL/POTT, 513-255-5132		10. SPONSORING/MONITORING AGENCY REPORT NUMBER WL-TR-96-2087		
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Computations of the velocity fields for Langston turbine blade cascades with solidities of 1.075 and 0.84 have been carried out at Reynolds numbers of 50K, 100K, 200K, 441K, 1000K, and 2000K. A second cascade investigated at Reynolds numbers of 50K and 100K uses the Langston airfoil which has been modified by extending the trailing edge, resulting in a solidity of 0.786. The computations were performed with Allison's Blade Vanc Interaction code. Computational results are presented for transition, separation, and reattachment.				
14. SUBJECT TERMS Turbine, Low Reynolds Number, Transition, Separation, Reattachment			15. NUMBER OF PAGES 15	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to **stay within the lines** to meet **optical scanning requirements**.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in.... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement.

Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

Low Reynolds Number Turbine Blade Cascade Calculations

Richard Rivir, Rolf Sondergaard, Michael Dahlstrom
Wright Laboratory, Aero Propulsion and Power Directorate
Wright Patterson AFB, Ohio

Elizabeth Ervin
Mechanical Engineering Department
University of Dayton
Dayton, Ohio

ABSTRACT

Computations of the velocity fields for Langston turbine blade cascades with solidities of 1.075 and 0.84 have been carried out at Reynolds numbers of 50K, 100K, 200K, 441K, 1000K, and 2000K. A second cascade investigated at Reynolds numbers of 50K and 100K uses the Langston airfoil which has been modified by extending the trailing edge, resulting in a solidity of 0.786. The computations were performed with Allison's Blade Vane Interaction code. Computational results are presented for transition, separation and reattachment.

Keywords: Turbine, Low Reynolds Number, Transition, Separation, Reattachment

1. INTRODUCTION

It is suspected that the inability to accurately predict the transition, separation, and reattachment at the low Reynolds numbers is associated with the high levels of turbulence and unsteadiness of the flow. A low pressure turbine typically operates at a chord Reynolds number of 10^6 at take off. This chord Reynolds number falls to 150,000 to 50,000 at altitude in a number of engines. Modern turbine blades have high aft loading so unpredicted transition, transition length and separations cause significant losses. C-17(F-117) engines as well as smaller engines with their associated smaller blades typically exhibit higher than predicted SFC during high altitude operation. Sharma[8] reported a near doubling of the measured loss coefficient when the chord Reynolds number is reduced from 300K to 50K with an additional operational loss of 0.8% in SFC over design calculations. Halstead et al., [5] have recently conducted an extensive experimental and computational investigation of low Reynolds number effects on both compressor and turbine blades. On the low pressure turbine blades which they investigated the wake induced turbulent transition region was coupled to the non wake region by an unusual calmed region. Existing codes which they investigated were unable to accurately describe the flows. The Allison Turbine Vane-Blade Interaction (VBI) code to be used in this study has demonstrated a modeling of the wakes interaction with the rotor and is a potentially useful code for this problem. This is the first phase of this study and results with out wakes for only a stationary rotor will be presented at this time.

2. COMPUTATIONAL RESULTS

The Langston cascade [6] was chosen as the geometry for investigation since it is a well documented geometry at higher Reynolds numbers, while still fairly representative of current low pressure turbine geometries. Experimental suction surface heat transfer coefficients have recently been obtained by Baughn et al.,[2] for the Langston cascade at low Reynolds numbers. The computational code used for the numerical simulation of the steady Navier-Stokes equations was the VBI code developed by the Allison engine company, Rao et al., [7] under U.S. Air Force contract. The grid used in this code is an

overlaid combination of a rectangular H grid and a body fitted hyperbolic O grid as shown in Figure 1. The rectangular grid is used to resolve the free stream flow and the O grid is used to resolve the regions of high shear associated with the boundary layer. Small values of y^+ have been employed in the calculation for the O grid spacing, with the first grid point at a y^+ of 1 or less. The steady state solution of the code is based on a five step Runge Kutta relaxation method that incorporates residual smoothing to accelerate convergence to the final solution. The code implements a Baldwin-Lomax [1] two-layer algebraic turbulence model and the Baldwin-Lomax point transition model. Transition occurs at the fixed recommended value of the turbulent coefficient of viscosity, $c_\mu=14$. Steady state residuals for these calculations are typically the order of 10^{-6} .

3. RESULTS AND DISCUSSION

The calculations were performed for the Langston cascade at chord Reynolds numbers of 50K, 100K, 200K, 441K, 1000K, and 2000K. Calculations for two solidities, or chord to pitch ratios, 1.075 (original Langston spacing) and 0.84, were investigated for all six Reynolds numbers. The locations of transition, separation, and reattachment are measured from the tangent to the leading edge and projected onto the x axis. This convention was also employed by Baughn et al., [1], in a linear Langston cascade, and Dring et al., [4], Blair et al., [2], and [3], in a large low speed steady state rotating Langston cascade.

The choice of the tangent to the leading edge to measure the location of transition, separation and reattachment may mask another effect. A small separation bubble was observed near the stagnation point that can alter the surface path length to the event (transition, separation, or reattachment) by up to 8% of the chord. This leading edge separation bubble is however not present for the Reynolds number of 50K.

Grid independence was investigated thoroughly for the original applications of the code. This investigation was conducted at the lowest applicable Mach number of the code and grid independence has been rechecked for this application. The results of the grid independence study are shown in Figures 2 and 3 by comparing the calculated pressure distributions and skin friction coefficients for three grids (66x25 H, 99x15 O), (99x51 H, 99x29 O), (99x99 H, 99x59 O). The pressure distributions of Figure 2 clearly indicate grid independence for the last two grids while the skin friction coefficient, a very sensitive indication of grid independence, very nearly indicates independence as the intermediate grid spacing is doubled in Figure 3. The standard grid spacing for the computations to be presented will be 99x51 for the H grid and 99x29 for the O grid.

4. EFFECTS OF REYNOLDS NUMBER AND SOLIDITY

Figures 4 through 7 present the results for cascade solidities (C/p) of 1.075. Figure 4 shows the skin friction distribution for a Reynolds number of 50K for the original Langston spacing, indicating separation at ($x/C=0.63$) and reattachment at ($x/C=0.83$). At a Reynolds number of 100K the skin friction coefficient oscillates in Figure 5 as the laminar flow tries to separate the turbulence model turns on keeping the flow attached. The oscillation in the skin friction coefficient disappear after a Reynolds number of 200K with the distributions approaching the high Reynolds number, 2000K, solution shown in Figure 6.

Figures 7 through 10 present the results for the 0.84 solidity cascade. The skin friction coefficient for the Reynolds number of 50K is shown in Figure 7, there are large changes in slope of the skin friction distribution before separation, then the zero crossing at separation, ($x/C=0.66$), and no reattachment. At a Reynolds number of 100K transition has occurred at $x/C=0.0213$, separation at 0.6, and reattachment at 0.87 as illustrated in Figure 8. The separation, for the low solidity case, $C/p=0.84$, continues to move forward until it stabilizes at an x/C of 0.57-0.6 and reattachment settling out at 0.8 after a Reynolds number of 200K. The vector velocity field for a Reynolds number of 441K is shown in Figure 9, with separation at 0.6 and reattachment at 0.8.

The distribution of the separation and reattachment location in % of x projected cord is shown in Figures 10 and 11 for both solidities. After a Reynolds number of 100K there is effectively no separation in this cascade for the solidity of 1.075 while the $C/p=0.84$ case remains separated for all

Reynolds numbers. The indicated transition location is shown in Figure 12 for both solidity ratios. The transition location moves forward as the Reynolds number is increased with the entire blade effectively turbulent after a Reynolds number of 441K for $c/p=1.075$. Transition has effectively occurred by a Reynolds number of 100K for $C/p=0.84$ as indicated in Figure 12.

The Langston airfoil was modified by extending the trailing edge until the radius of the trailing edge was reduced by 0.25 of that of the original blade. Extending the blade also results in a further reduction in solidity to $c/p=0.7857$. The separation occurs at $x/C=.515$ and reattachment occurs at $x/C=0.938$ for the 50K Reynolds number. The resulting blade profile is indicated by the outline of the vector velocity field in Figure 13 for the Reynolds number of 50K. The skin friction coefficient at a Reynolds number of 100K is presented in Figure 14. A small separation bubble occurs at $x/C=0.515$, then reattaches immediately at 0.607. The improvement resulting from the sharp trailing edge blade may be seen by comparing Figure 14 with Figure 8 which shows no reattachment at 100K, however the aft loading has not returned.

5. SUMMARY

The presented results demonstrated the sensitivity of separation, and reattachment to Reynolds number and solidity for the range of Reynolds numbers of 50K to 2000K. The Langston profile with a pitch to chord spacing of 1.18 showed separation for all values of Reynolds numbers investigated in this study. The Langston profile with a pitch to chord spacing of 0.93, the original Langston spacing, showed separation at a Reynolds number of 50K, oscillating transition at 100K and attached flow for all other Reynolds numbers. A fixed value of c_u was used in the calculations. Transition location for the Reynolds number range of 50K to 2000K was presented. Sharpening the trailing edge and covering the suction surface provided a simple cure for the separation but did not return the high aft loading obtained at high Reynolds numbers.

6. REFERENCES

1. Baldwin, B. S., and Lomax, H., 1978, "Thin-Layer Approximation and Algebraic Model for Separated Turbulent Flows," AIAA Paper 78-0257.
2. Baughn, J. W., Butler, R. J., Byerley, A. R., and Rivir R. B., August 1995, "An Experimental Investigation of Heat Transfer, Transition and Separation On Turbine Blades at Low Reynolds Number and High Turbulence Intensity," 1995 ASME International Mechanical Engineering Congress and Exposition.
3. Blair, M. F., 1994, "An Experimental Study of Heat Transfer in a Large Scale Turbine Rotor Passage," *ASME Journal of Turbomachinery*, Vol. 116, pp. 1-13.
4. Blair, M. F., Dring, R. P., and Joslyn, H. D., 1989, "The Effects of Turbulence and Stator/ Rotor Interactions on Turbine Heat Transfer: Part 2-Effects of Reynolds Number and Incidence," *ASME Journal of Turbomachinery*, Vol. 111, pp. 97-10387-96.
5. Dring, R. P., Blair, M. F., and Joslyn, H. D., 1986, "The Effects of Inlet Turbulence and Rotor Stator Interactions on the Aerodynamic and Heat Transfer of a Large Scale Rotating Turbine Model, Volume 11-Heat Transfer Data Tabulation, 15% Axial Spacing," NASA CR 179467, UTRC-R86-956480-2.
6. Halstead, D. E., Whisler, D. C., Okiishi T. H., Walker G. J., Hodson H. P., Shin H. W., "Boundary Layer Development in Axial Compressors and Turbines, Part 3 of 4: LP Turbines," ASME 95-GT-463, IGTI, June 1995.
7. Langston, L. S., Nice, M. L., and Hopper, R. M., 1977, "Three Dimensional Flow within a Turbine Cascade Passage," *Journal for Engineering and Power*, Vol. 99, pp. 21-28.
8. Rao, K. V., Delaney, R. A., and Dunn M. G., "Vane-Blade Interaction in a Transonic Turbine, Part 1 Aerodynamics," May-June 1994, *Journal of Propulsion and Power*, Vol. 10 No. 3, pp. 305-311.
9. Sharma, O. P., Tanrikut, S., May 1994, "Unsteady Flows in Turbines-Impact on Design Procedure," AGARD Lecture Series 195, *Turbomachinery Design Using CFD*.




Figure 1. Overlaid H and O Grids, H:99x51,O: 99x29




Figure 2. VBI Blade Pressure Coefficient / Grid Independence Comparison




Figure 3. Grid Independence/Resolution, Chord $Re = 441K$, H Grid =99x51, O Grid=99x29, Chord/Pitch=0.84




Figure 4. Skin Friction Distribution, Chord $Re = 50K$, H Grid =99x51, O Grid=99x29, Chord/Pitch=1.075




Figure 5. Skin Friction Distribution, Chord $Re = 100K$, H Grid = 99x51, O Grid = 99x29, Chord/Pitch = 1.075




Figure 6. Skin Friction Distribution, Chord $Re = 2000K$, H Grid = 99x51, O Grid = 99x29, Chord/Pitch = 1.075




Figure 7. Skin Friction Distribution, Chord $Re = 50K$, H Grid = 99×51 , O Grid = 99×29 , Chord/Pitch = 0.84




Figure 8. Skin Friction Distribution, Chord $Re = 100K$, H Grid = 99×51 , O Grid = 99×29 , Chord/Pitch = 0.84




Figure 9. Velocity Vector Profiles, Chord $Re = 441K$, H Grid = 99×51 , O Grid = 99×29 , Chord/Pitch = 0.84




Figure 10. Separation Location in % Projected Chord




Figure 11. Reattachment Location in % Projected Chord




Figure 12. Transition Reynolds Number Dependence in % Projected Chord




Figure 13. Vector Velocity Profile Thinned Blade, Chord $R_e = 50K$, H Grid = 99x51, O Grid = 99x29, Chord/Pitch = 0.84




Figure 14. Skin Friction Coefficient Distribution Thinned Blade, Chord $R_e = 100K$, H Grid = 99x51, O Grid = 99x29, Chord/Pitch = 0.7857